

COMP energy

EV 130.5 150W




Technical Specifications

Component	-	Woofers
Size	mm (in.)	130 (5)
Power handling	W peak	150
	W continuous	50
Impedance	Ω	4
Frequency response	Hz	70 ÷ 6k
Sensitivity	dB SPL	93
Magnet size D-d-h	mm (in.)	80 x 32 x 13 (3.15 x 1.26 x 0.5)
Voice coil \varnothing	mm (in.)	25 (1)
Magnet	-	High density flux ferrite
Cone	-	Water repellent pressed paper
Weight of one component	kg (lb.)	0,7 (1.54)

Electro-Acoustic Parameters

D	mm	110
Xmax	mm	3
Re	Ω	3,1
Fs	Hz	82
Le	mH	0,18
Vas	l	6,05
Mms	g	7,9
Cms	mm/N	0,47
BL	T-m	4
Qts	-	0,68
Qes	-	0,8
Qms	-	4,6
Spl	dB	93



A	130 mm	5.12 in.
A3	150 mm	5.9 in.
B	119 mm	4.68 in.
C	57 mm	2.24 in.
D	50 mm	1.96 in.

1. V-cone® for best off-axis response and clear mid-high frequency detail.
2. Water-repellent treated paper cone; butyl rubber surround.
3. Pure copper voice coil, wound on aluminium former, for exceptional thermal and mechanical capacity.
4. Large motor assembly for excellent control of voice coil.
5. Low carbon content plates for maximum magnetic permeability and high heat dissipation.
6. Rubber magnet cover provides damping to the basket and motor structure and protects from abrasions and damages.
7. DIN size basket coated with scratch-proof, corrosive-resistant material.
8. Tin-plated, high current terminals.
9. Silver-plated lead wires, for maximum reliability and conductivity.
10. Epoxy glue for basket and motor system provides perfect coupling.
11. Curve memory Nomex spider for consistent, reliable performance.

