

COMP HI ENERGY

HT 20 100 Watt



Technical Specifications

Component	Tweeter	
Size	mm	20 (3/4")
Power Handling	W peak	100
	Hi-pass filtered 3.0 kHz @ 12 dB Oct.	
Impedance	Ω	4
Frequency response	Hz	1.9k ÷ 22k
Sensitivity	dB/SPL	91
Outer \varnothing	mm	38
Mounting \varnothing	mm	35
Total depth	mm	22
Mount. depth	mm	14
Magnet size	mm	19
Weight of one speaker	kg	0,035
Voice coil \varnothing	mm	20



- 1 Tetolon® soft dome tweeter.
- 2 20mm \varnothing , ferrofluid-cooled mobile voice coil.
- 3 High energy Neodymium magnet.
- 4 Rear acoustic chamber.
- 5 Revolving support and accessories for factory location and flush mounting.
- 6 Very flexible, high current input cable.



Electro-Acoustic Parameters

D	mm	20
Xmax	mm	-
Re	Ω	3,5
Fs	Hz	1600
Le	mH@1kHz	0,13
Le	mH@10kHz	0,02
Vas	l	-
Mms	g	0,2
Cms	mm/N	0,05
BL	T-m	1,40
Qts		0,67
Qes		3,00
Qms		0,86
Spl (1m/2,83V)	dB	91

