

# SX 300D.1

SUBWOOFER

## 3200 W



### TECHNICAL SPECIFICATIONS


Component	SPL Dual Coil Subwoofer	
Size	mm (in.)	300 (12)
Power handling	W peak	3200
	W continuous	800
Impedance	$\Omega$	2 + 2
Freq. response	Hz	28 ÷ 700
Sensitivity	dB/SPL	91
Magnet size	mm	180 x 75 x 45
	(in.)	(7 x 3 x 1.8)
Voice coil $\varnothing$	mm (in.)	65 (2.3)
Magnet	Double magnet, High density flux ferrite	
Cone	Pressed paper	
Total driver displacement	l (cu.in.)	2,5 (153)
Weight of one component	kg (lb.)	11,8 (26)
X-mech*	mm (in.)	23 (0.9)

\*X-mech massima escursione meccanica, indica il range di movimento in zona di funzionamento lineare dell'altoparlante, in entrambi i sensi

### ELECTRO-ACOUSTIC PARAMETERS

D	mm	253
Xmax	mm	14
Re*	$\Omega$	4
Fs	Hz	46
Vas	l	20
Mms	g	202
Cms	mm/N	0,06
BL	T•m	21,6
Qts		0,48
Qes		0,51
Qms		8,2
Spl	dB	91

\* Bobine in serie



A	318 mm (12.5 in.)
B	284 mm (11.2 in.)
C	198 mm (7.8 in.)
D	170 mm (6.7 in.)

1. High magnetic permeability plates provide constant, even flux.
2. Large double magnet, for perfect control under high power, very high excursion conditions for high SPL performance.
3. Four-layer aluminium voice coil; for unheard-of thermal capability.
4. Back plate venting holes, for optimal thermal dissipation.
5. Back vented spider support; for perfect symmetry under high excursion while providing increased thermal dissipation.
6. High-current, screw terminals, for large gauge wires.
7. Tinsel lead wires are integrated in the spider; for maximum reliability and conductivity.
8. Double wide-wave, resin-bonded fibre spider; for consistent parameters and reliability.
9. High density foam surround; for linear movement, even under extreme excursion.
10. Water-repellent, pressed paper cone.
11. Aluminium ring within the pole piece reduces impedance modulation at high excursion.

