

COMP HI ENERGY

HT 25 120 Watt



Technical Specifications

Component	Tweeter	
Size	mm	25 (1")
Power Handling	W peak	120
	Hi-pass filtered 2.5 kHz @ 12 dB Oct.	
Impedance	Ω	4
Frequency response	Hz	1.6k ÷ 22k
Sensitivity	dB/SPL	92
Outer \varnothing	mm	44
Mounting \varnothing	mm	41
Total depth	mm	26
Mount. depth	mm	15
Magnet size	mm	24,5
Weight of one speaker	kg	0,06
Voice coil \varnothing	mm	25



- 1 Tetolon® soft dome tweeter.
- 2 25mm \varnothing , ferrofluid-cooled mobile voice coil.
- 3 High energy Neodymium magnet.
- 4 Rear acoustic chamber.
- 5 Revolving support and accessories for factory location and flush mounting.
- 6 Very flexible, high current input cable.



Electro-Acoustic Parameters

D	mm	25
Xmax	mm	-
Re	Ω	3,5
Fs	Hz	1400
Le	mH@1kHz	0,17
Le	mH@10kHz	0,02
Vas	l	-
Mms	g	0,2
Cms	mm/N	0,06
BL	T-m	1,80
Qts		0,63
Qes		2,00
Qms		0,90
Spl (1m/2,83V)	dB	92

